

WASH REGULARLY

Wash whenever the car appears dirty. Contaminants that remain on the vehicle wrap will be more difficult to remove during cleaning.




1. Rinse off as much dirt and grit possible with a spray of water.

For difficult contaminants such as tar, bird droppings, etc. see below.



2. Use a wet non-abrasive detergent such as a soft, clean cloth or sponge.

Rinse thoroughly with clean water.



3. To reduce water spotting immediately use a squeegee to remove water and finish with a microfiber cloth.



DO NOT USE CAR WASHES



HANDWASHING IS THE BEST CLEANING METHOD.

Pressure washing may be used under these conditions:

- Ensure water pressure is below 2000 psi
- Keep water temp. below 80°C (180°F)
- Use a spray nozzle with a 40 degree wide angle
- Keep the nozzle 1 foot away from the graphic

DIFFICULT CONTAMINANTS

Soak difficult contaminants such as bug splatter, bird droppings, tree sap, etc. for several minutes in **VERY HOT, SOAPY WATER**. Rinse thoroughly and dry. For further cleaning, isopropyl alcohol or denatured alcohol may also help. Spot clean the contaminants. Do not use rough scrubbing or abrasive tools. Wash and rinse off all residue immediately.

FUEL SPILLS

Wipe off immediately to avoid degrading the vinyl adhesive. Wash, rinse and dry as soon as possible.

STORAGE



During the day store in a garage or in a shaded area. At night, protect the car from dew or rain, which may contain acidic pollutants.

When a garage is not available consider using a cloth or cover at night.

If your wrap starts to discolor, turn brown, or crack immediately have a professional remove the wrap film from the vehicle to avoid damaging the underlying paint.